

**(19) World Intellectual Property Organization
International Bureau**



(43) International Publication Date
30 October 2003 (30.10.2003)

PCT

(10) International Publication Number
WO 03/089152 A1

(51) International Patent Classification⁷: B05B 11/00

(21) International Application Number: PCT/GB03/01685

(22) International Filing Date: 17 April 2003 (17.04.2003)

(25) **Filing Language:** English

(26) Publication Language: English

(30) Priority Data:
0208806.0 17 April 2002 (17.04.2002) GB

(71) Applicant (for all designated States except US): RIEKE CORPORATION [US/US]; 500 West 7th Street, Auburn, IN 46706 (US).

(72) Inventors: and

(75) **Inventors/Applicants (for US only): LAW, Brian, Robert** [GB/GB]; 11 Meadhurst Road, Western Park, Leicester, Leicestershire LE3 6FR (GB). **PRITCHETT, David, John**

[GB/GB]; 41 Derbyshire Avenue, West Hallam, Derbyshire DE7 6HJ (GB). **SPENCER, Jeffrey, William** [GB/GB]; 5 Harene Crescent, Kirby Muxloe, Leicester, Leicestershire LE3 3HS (GB).


(74) Agents: STONER, G., Patrick et al.; Mewburn Ellis, York House, 23 Kingsway, London, Greater London WC2B 6HP (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW).

[Continued on next page]

(54) Title: PUMP DISPENSERS



(57) Abstract: Pump dispensers are specially adapted for inverted use. One feature, especially useful in a foam dispenser having both an air cylinder (5) and a liquid cylinder (6) with respective pistons, is an intake conduit arrangement to increase the clearance of liquid from the container. An intermediate shell (7) fits over the upright liquid cylinder body (6) and carries an inlet valve (73) positively urged upwardly to the closed position, to prevent leaking. A conduit shell (8) fits over the intermediate shell (7) and creates an intake conduit (85) extending down the side of the liquid cylinder to an intake opening (81) lower down the pump body.

WO 03/089152 A1